

ECUcore-1021

Communication Controller for High Performance Applications

ECUcore-1021 is a compact and cost-effective module that is especially suitable for the use in complex networked applications. With its high number of available communication interfaces and the dual-core 1GHz CPU, the module offers outstanding performance at low power dissipation.


ARM 32-bit Cortex[™]-A7 dual-core processor

Long-term availability

High number of available I/O

Low power dissipation

Pre-installed Linux OS





Distributed by **NVUW**

Specifications

Controller NXP QorlQ LS1021A dual-core

communication processor

Core Architecture Dual-core Cortex®-A7, each with 1GHz,

FPU and Neon co-processor

RAM 1GB DDR3L-1600MT (opt. ECC)

Flash 2x 64MB

Communication 3x 1GbE (1 PHY on-board), 4x CAN,

USB 3.0, 2x PCIe 2.0, 7x UART, 2x UCC on a ULite QUICC Engine (32-bit RISC co-processor)

Mass Storage SATA 3.0, SDHC/MMC/eMMC

Video 24-bit RGB (12-bit DDR pin LCD interface)

Audio 4x SAI/I2S, 1x SPDIF, 1x ASRC

I/O FlexTimer (PWM, CNT, ENC), I2C, SPI,

GPIO, 8/16-bit A/D-Bus (FPGA)

Peripherals Temperature, RTC, watchdog

Board Connector 220-pin connector (COM Express form

factor with customized flexible pinout)

Board Dimensions 55x84 mm (COM Express® mini)

Power Supply 3.3V DC single voltage **Power Dissipation** 4.5W (under typical load)

Temperature Range -40°C...85°C (Storage: -55°C...125°C)

MTBF Predictions min. 650.000h @ 40°C

Availability 15 years (NXP Longevity Program)

Thermal Management Single heat spreader plate, passive cooling

Security and Fuses, System Monitoring, Secure

IP Protection Boot, Firmware Protection, QorlQ Trust

(optional) Architecture

Others 1x ADC input

(optional)

For detailed configuration options please contact us!

The ECUcore-1021 is a System on Module based on the NXP QorlQ LS1021A dual-core processor. The LS1021A offers a high number of communication and I/O interfaces combined on a single chip. This enables the customer to configure the chip and to define the available interfaces on the connector independently. This flexibility enables the customer to use the ECUcore-1021 in a wide variety of application scenarios; from simple HMI to a complex network device.

Compared to similar CPUs, the processor used provides high performance at comparatively lower power dissipation. It can be used at industrial environment with high temperature without active cooling. This does not only reduce the needed board space and make the module design compact, but also is cost-effective.

About SYS TEC electronic

SYS TEC electronic is a system house for customized electronic systems. Founded in 1990 in Germany, SYS TEC electronic has more than 25 years of experience providing a comprehensive service from consulting to OEM integration and series production or transfer of technology to our customers in the field of industry, transportation, communication, power management and computing.



Software Support

- Linux OS Board Support Package with Real Time preempt patches applied
- Pre-integrated IDE with cross-platform toolchain
- Communication protocols (optional):
 POWERLINK, CANopen, EtherCAT, Profinet, Profibus, Modbus
- IEC 61131-3 PLC Runtime Systems (optional):
 CODESYS V3.5 (3S) or OpenPCS (infoteam Software)
- Target- and Web-Visualization



Development Kit


The cost-effective Development Kit enables a quick start of application development based on NXP QorIO LS1021A and ECUcore-1021. The important interfaces are already configured at the Development Board.

Application Kit


The Application Kit is optimized in its functionality and can serve as a basis for the development of own devices. It is particular convenient for the use in modern industrial applications that requires secure communication and can also be used as an IoT-Gateway.

The Application Carrier Board offers a comprehensive configuration of interfaces. The components on the Carrier Board were selected on the basis of their long-term availability and reliable operation in industrial environments.

The Application Carrier Board with ECUcore-1021 can be integrated in a ready housing solution and thus be used as a finished product solution.



Development Board



Application Carrier Board

Development Board



Application Carrier Board with optional mSATA and WiFi Modules

Kit contents:

- ECUcore-1021
- Development Board or Application Carrier Board
- Virtual machine with IDE and toolchain
- Board schematics, BOM of the Carrier Board
- Email & web support

We are looking forward to discussing with you your very own customized Development Kit or ECUcore-1021 configurations.

Please contact our experts!



4001046 ECUcore-1021 KIT-173 Development KIT KIT-174 Application KIT

For quotations please contact us: +49 3765 38600-2110 sales@systec-electronic.com